

# Product data sheet

## WRM-24



Receiving module for activating automatic doors and window drives with 24 V DC

### AREAS OF APPLICATION

- Activation of GEZE automatic doors and window drives via the GEZE wireless program
- Flush-mounted installation



### PRODUCT FEATURES

- Encrypted communication via rolling code with up to 74 trillion code combinations
- Simple teach-in via learn button with acoustic feedback
- Up to 85 radio transmitters can be taught
- Integrated DIP switch to select different modes of operation
- Pulse mode, pulse and continuous mode, deadman mode, or self-locking mode
- Smallest housing dimensions for integrated installation within a flush-mounted box
- Two outputs for individual connection possibilities

### TECHNICAL DATA

Productname	WRM-24
Operating current	12.5 mA
IP rating	IP20
Type of installation	Flush-mounted installation
Transmission frequency	433.93 Mhz
Operating temperature	0 °C - 50 °C

### VARIANTS / ORDER INFO

Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
WRM-24 receiving module	52 x 47 x 23 mm (W x H x D), for installation in a standard flush-mounted box / 24 V DC operating voltage, pulse mode or pulse and permanent mode	131213	black	52 x 52 x 47 x 23 mm	24 V DC