

# Product data sheet OL 320



Surface-mounted fanlight opener with an opening width of 320 mm

## **AREAS OF APPLICATION**

- → Convenient daily ventilation for rooms and staircases
- → For windows with high leaf weights up to max. 250 kg
- → Inward opening bottom-hung windows
- → Automation by E 212 electric linear drive
- ightarrow Installation on wooden, plastic or aluminium windows
- → Frame installation

# **OL 320**



#### **PRODUCT FEATURES**

- → Achieves the full opening width of 320 mm for all leaf heights
- → The opening width can be adjusted
- → Little space necessary thanks to flat design of the scissors
- ightarrow Safety button on the scissors shows scissors engagement in spherical head of leaf bracket
- → Integrated leaf locking mechanism in the scissors ensures secure locking
- → Scissor unhooking by pressing the release button facilitates window cleaning from inside and outside
- → Unhinging inhibitor offers additional safety
- → Lock carrier and additional locking mechanisms increase safety and air-tightness
- → The scissors and the link arm can be installed from the front
- → Leaf bracket fits all overlap heights and materials

#### TECHNICAL DATA

Productname	OL 320		
Length	436 mm		
Depth	65 mm		
Height	26 mm		
Opening width (max.)	320 mm		
Leaf width (min.)	680 mm		
Leaf height (min.)	400 mm		
Leaf weight (max.)	250 kg		
Fitting stroke	70 mm		
Adjustable opening width (stroke reduction)	Dependent		
Leaf locking mechanism integrated in the scissors	Yes		
Scissor unhooking by release button	Yes		
Unhinging inhibitor	Yes		

# **OL 320**



# ACCESSORIES

## **GRIPPING AND CLEANING SCISSORS (FPS)**

For fanlight openers for additional protection of bottom-hung leaves



Designation	Description	Ident-No.	Colour
Gripping and cleaning scissor stay (FPS) Size 1	FPS size 1	030249	Galvanised
Gripping and cleaning scissor stay (FPS) Size3	FPS size 3	030251	Galvanised
Gripping and cleaning scissor stay (FPS) Size 2	FPS size 2	030250	Galvanised