

Product data sheet

GC 171 *



Wireless module for wireless connection of wireless components to GEZE hold-open systems

AREAS OF APPLICATION

- Installation in listed buildings without structural changes (cable routing)
- Retrofitting or extension of existing systems



PRODUCT FEATURES

- No cable connection needed between lintel-mounted detector and ceiling-mounted detector or manual trigger switch
- Simple coupling of the wireless components
- Connection of up to six wireless devices
- Mixed installation (wireless/wired) possible
- Low servicing costs due to long battery life of five years

TECHNICAL DATA

Productname	GC 171 *
Dimensions	177 x 30 x 18 mm
Ambient temperature	-5 °C - 50 °C
Connection of additional smoke switches	6
Visual status display	Yes
Supply voltage	24 V DC
IP rating	IP20
Material	Plastic
Type of installation	Wall, Lintel
Line-feed	Below, At the side
Area of application	Inside

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Supply voltage	Dimensions
GEZE GC 171 wireless module *	for the wireless connection of wireless components (GC 172 wireless smoke detector; GC 173 wireless thermal detector; GC 175 wireless input module) on GEZE hold-open systems.	163051	anthracite	24 V DC	177 x 30 x 18 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.