

Product data sheet Perlan AUT-NT glass with 30 mm glass clamping plate



Automation for Perlan on glass doors with up to 80 kg leaf weight

AREAS OF APPLICATION

- → Sliding door automation for Perlan on light to medium-weight interior doors
- → Particularly suitable for private living areas
- → Single and multiple-leaf glass sliding doors
- → Mounting to the wall and also to the ceiling via additional ceiling brackets
- \rightarrow Not for escape or rescue routes



PRODUCT FEATURES

- → For automation of Perlan internal sliding doors with a leaf weight of max. 80 kg
- → Adjustable comfort and safety functions
- → Max. speed can be set up to 0.3 m/s
- → Low-energy sliding door drive in accordance with EN 16005

TECHNICAL DATA

Productname	Perlan AUT-NT glass with 30 mm glass clamping plate
-------------	---

PART

FLOOR GUIDE FOR GLASS LEAF

Floor guide with variable adjustment for glass thicknesses 8, 10 and 12



Designation	Description	Ident- No.	Colour	Glass thickness
Floor guide for glass leaf (adjustable)	with variable adjustment for glass thickness 8–13.5 mm, with frieze band for noise reduction with structured glass surfaces, without attachment material	120417	silver- coloured	8 - 13.5 mm

SET CAPS FOR GLASS CLAMPING PLATE 30 MM *

End cap for glass clamping plate 30, set comprising 2 pieces





Designation	Description	Ident- No.	Glass thickness
Set caps for glass clamping plate 30 mm	2 caps for installation on the outer leaf side for attachment of the continuous cover and side caps, necessary where the cover panel projects > 200 mm beyond the glass clamping plate	142373	8 - 12 mm

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com



GLASS CLAMPING PLATE 30 MM SET, CONTINUOUSLY BLENDED

Glass clamping plate 30 for leaf weights up to 80 kg with continuous



Designation	Description	Ident- No.	Glass thickness
Glass clamping plate 30 mm set, continuously blended	Consisting of 2 glass clamping plates incl. suspension bolts, continuous bespoke cover and end caps, EV1 or stainless steel optic, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142368	8 - 12 mm

GLASS CLAMPING PLATE 30 MM SET, WITH COVERING

Glass clamping plate 30 mm including cover for leaf weights up to 80 kg



Designation	Description	Ident- No.	Colour	Glass thickness
Glass clamping plate 30 mm set, with covering	Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142366	Stainless steel optic	8 - 12 mm
Glass clamping plate 30 mm set, with covering	Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142367	according to RAL	8 - 12 mm
Glass clamping plate 30 mm set, with covering Consisting of 2 glass clamping plates incl. suspension bolts, individual cover profiles and end caps, up to 80 kg leaf weight, for 8–12 mm toughened safety glass		142365	EV1	8 - 12 mm

GLASS CLAMPING PLATE 30 MM SET, WITHOUT COVER

Glass clamping plate 30 for leaf weights up to 80 kg without cover





Designation	Description	ldent- No.	Glass thickness
Glass clamping plate 30 mm set, without cover	Consisting of 2 glass clamping plates incl. suspension bolts, up to 80 kg leaf weight, for 8–12 mm toughened safety glass	142364	8 - 12 mm

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com



TRACK PERLAN 140

Track for sliding door fitting



Description	Ident-No.	Colour
with countersunk drill holes (prepared for Perlan SoftStop)	142518	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	128660	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	128662	Stainless steel optic
with countersunk drill holes (prepared for Perlan SoftStop)	135048	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	135047	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	142519	EV1
with countersunk drill holes (prepared for Perlan SoftStop)	135046	EV1
	with countersunk drill holes (prepared for Perlan SoftStop)	with countersunk drill holes (prepared for Perlan SoftStop) 142519

ACCESSORIES

KFT ELBOW SWITCH

Plastic elbow switch, IP rating IP20, for activation of automatic doors



Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
KFT elbow switch	Very flat design, IP rating IP20	114077	stainless steel colour	90 x 179 x 23 mm	Surface-mounted
KFT elbow switch	Very flat design, IP rating IP20	114078	white	90 x 179 x 23 mm	Surface-mounted

DOOR STOP

End stop for sliding leaves



Designation	Ident-No.
Door stop	000339
Door stop	000342

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com



LSG GLASS / METAL GLUE *

Glass metal glueing kit for connecting aluminium brackets with glass panes



Designation	Description	Ident-No.
LSG glass / metal glue 50 g *	for up to 30 sliding panels	133039

POWER SUPPLY PERLAN AUT-NT *

Power supply for Perlan NT control unit



Designation	Ident-No.	Colour	Supply voltage
Power supply Perlan AUT-NT *	139994	black	115 - 230 V AC

HEIGHT COMPENSATION MECHANISM / CEILING DISTANCE SET, WITH VARIABLE ADJUSTMENT

Height compensation with variable adjustment for ceiling installation of tracks



Designation	Description	Ident- No.
Height compensation mechanism / ceiling distance set, with variable adjustment	6 pieces, height compensation mechanism with variable adjustment from 13 mm to 18 mm. For use for ceiling mounting using clip-on cover 100/145 as well as for general use on uneven ceilings	138099

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com 2024-05-05T14:40:24Z



SET CONTROL UNIT WITH PUSH BUTTON PERLAN AUT-NT

Control unit and push button for Perlan AUT



Designation	Ident-No.	Colour
Set control unit with push button Perlan AUT-NT	141151	white

DOOR PULL HANDLE, CONFIGURED *

Push bar - round design for installation on glass leaves



Designation	Ident-No.	Colour
Door pull handle, configured *	127616	Stainless steel

TOOTHED BELT PERLAN AUT-NT / AUT

Toothed drive belts for automatic sliding door fittings



Designation	Ident-No.	Colour
Toothed belt Perlan AUT-NT / AUT	141500	black

TOOTHED BELT PERLAN AUT-NT / AUT 2, BESPOKE

Toothed drive belts for automatic sliding door fittings



Designation	Ident-No.	Colour
Toothed belt Perlan AUT-NT / AUT 2, bespoke	141561	black



FLOOR GUIDE SET GLASS GUIDE

Floor guide for glass sliding leaves for glass thickness 8, 10 and 12 mm



Designation	Description	Ident-No.	Colour	Glass thickness
Floor guide for glass leaf (stainless steel)	For 8, 10, 12 mm glass	134990	Stainless steel	8 - 12 mm

COMPLETE CLIP-ON COVER SET 100

Clip-on cover for covering Perlan door fitting systems



Designation	Description	Ident-No.	Type of installation
Complete clip-on cover set 100	for wall and ceiling mounting, continuous cover, bespoke configuration	138098	Wall, Ceiling

LSG GLUEING BRACKET SET *

Aluminium glueing bracket for LSG and glass clamping plate 30



Designation	Description	Ident-No.
LSG glueing bracket set	for use with LSG in connection with glass clamping plate 30 mm, for 2 clamping plates, without adhesive	142386

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com 2024-05-05T14:40:24Z

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.