

Product data sheet E 212 230 V *



Electric linear drive for automation of fanlight openers

AREAS OF APPLICATION

- ightarrow Automation of GEZE OL 90, OL 95 N and OL 320 fanlight openers
- ightarrow Natural ventilation in the façade area
- ightarrow Inward-opening bottom-hung leaves
- ightarrow Installation on wooden, PVC or metal windows
- ightarrow Frame installation



PRODUCT FEATURES

- ightarrow Cost-effective and simple motorised solution for activating several scissors
- ightarrow Can be integrated perfectly into the façade design thanks to its slim and discreet look
- ightarrow Opening width variably adjustable over stroke length and can be adjusted as necessary
- ightarrow Load cut-off and integrated limit switch as well as stroke are adjustable
- ightarrow Completely pre-mounted assembly groups facilitate installation

TECHNICAL DATA

Productname	E 212 230 V *
Space needed on frame (min.)	Necessary space should be determined individually
Space requirement on leaf (min.)	Necessary space should be determined individually
Compressive force	1500 N
Tensile force	1500 N
Operating voltage	230 V AC
Current consumption	0.2 A
Power consumption	50 W
Duty rating	25 %
Min. core cross section	1.5 mm ²
Service temperature	-20 - 60 °C
IP rating	IP42
Type of stroke shortening	Mechanical
End position cut-off extended	Limit switches
End position cut-off retracted	Limit switches
Overload cut-off	Yes
KNX ability	No
Bottom-hung window INWARD-opening frame installation	Yes

VARIANTS / ORDER INFO

Designatio n	Description	ldent-No.	Colour	Stroke	Operating voltage
E 212 R1	230 V with 1 relay for group control via 1 selector switch	020835	EV1	70 mm	230 V AC
E 212 R	230 V with 2 relays, for group control via any number of vent switches	005428	EV1	70 mm	230 V AC
E 212 R1	230 V with 1 relay for group control via 1 selector switch	020839	white RAL 9016	70 mm	230 V AC
E 212 R	230 V with 2 relays, for group control via any number of vent switches	015435	white RAL 9016	70 mm	230 V AC
E 212 R1	230 V with 1 relay for group control via 1 selector switch	020838	according to RAL	70 mm	230 V AC
E 212 R	230 V with 2 relays, for group control via any number of vent switches	006683	according to RAL	70 mm	230 V AC



ACCESSORIES

SYNCHRONISING UNIT E 212 R1 230 V

Synchronising unit for commissioning 230 V drives



Designation	Ident-No.	Colour
Synchronising unit for GEZE E 212 R1 230 V electric drive	026762	white

CONNECTING UNIT E 212 *

To couple the E 212 with the OL 320 scissors



- **1**

Designation	Description	Ident-No.	Colour	Dimensions
Coupling for E 212 *	To couple the E 212 with the OL 320 scissors	008800	silver-coloured	40 x 22 x 22 mm

SAFETY SCISSORS NO. 35

For protection of bottom-hung leaves

Designation	Description	Ident-No.	Colour
Safety scissors no. 35	Fix pack available from stock (10 pieces), minimum leaf height 300mm	014499	Galvanised

SAFETY SCISSORS NO. 60

For protection of bottom-hung leaves



Designation	Description	Ident-No.	Colour
Safety scissors no. 60	Fix pack available from stock (10 pieces), minimum leaf height 700mm	133814	Galvanised

ROD COUPLING OL 90 *

To couple the E 212 with the OL 90 N, OL 90 N top-hung outward opening and OL 95 scissors and to connect two rods



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.